



RENITHERM[®] PMW Primer

Transparent Waterborne Primer for Renitherm[®] PMW

Uses:	For substrates without sufficient bonding of Renitherm [®] PMW basecoat, as saturation of high absorbent surfaces, as improvement of adhesion of the fire retardant coating on sleek surfaces. Transparent polymer, fast drying.
Colour	Transparent
Application	<ul style="list-style-type: none">• application by brushing, rolling, spraying• temperature during application and drying time > 5 °C• notice dew point• sanding of wooden surface• stir well before applying• no thinning• tip size : airless : 0.013" / air: 1.2 mm• coverage rate : 60 – 100 g/m²
Consumption	60 - 100 g / m ²
Preparation of substrate	Clean from dust, grease, wax or resins. Remove old coatings.
Application hints	Stir well before use. Don't apply below +10°C and >80% R.H. Apply undiluted in supply viscosity.
Cleaning of equipment	With water
Drying time	Renitherm [®] PMW and Renitherm [®] PMW (P) can be applied after 4 hrs
Flash point	n/a
Density	Approx. 1,00 g / cm ³ at 20 °C

Packing	5 kg cans
Transport classification	VbF: n/a; RID/ADR: n/a
Storage	Min 12 months in original closed containers.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should not therefore be constructed as guaranteeing specified properties of products described or their suitability for a particular application. Any existing industrial property rights must be observed. The quality of our products is guaranteed under our General Conditions of Sale.



RENITHERM®



AUDAX-Keck GmbH, Weiherstr. 10, 75365 Calw / Germany



+49 7051 1625-0



+49 7051 1625-50



fire@audax.de

www.audax.de